


# Delock Cable DisplayPort 1.2 male > DVI 24+1 male passive 4K 30 Hz 3 m black

## Description

This cable by Delock enables the connection between devices, e.g. a monitor, with DVI connector to a DisplayPort interface.



ca. 3 m

## Specification

- Connectors:
  - 1 x DisplayPort male >
  - 1 x DVI 24+1 male with screws
- Chipset: Parade PS8402A
- DVI-D (Dual Link), VGA not wired
- DisplayPort 1.2a specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: DisplayPort input > DVI output
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Twisted-pair cabling
- Copper conductor
- Contacts gold-plated
- Triple shielded cable
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Colour: black
- Length without connectors: ca. 3 m

## System requirements

- A free DisplayPort DP++ female

## Package content

- DisplayPort to DVI cable

## Item no. 85314

EAN: 4043619853144

Country of origin: China

Package: Poly bag



## Images



General	
Specification:	DisplayPort 1.2a
Interface	
Connector 1:	1 x DisplayPort 20 pin male
Connector 2:	1 x DVI 24+1 male with screws
Technical characteristics	
Chipset:	Parade PS8402A
Data transfer rate:	3.96 Gb/s
Maximum screen resolution:	1920 x 1080 @ 60 Hz
Physical characteristics	
Cable diameter:	6 mm
Connector finishing:	gold-plated
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	30 AWG
Shielding:	triple
Length:	3 m
Colour:	black