

OVERVIEW





| 1. Optical drive * | 9. Line-out (3.5mm) |
|--|---|
| 2. Power button | 10. Flex IO * |
| 3. Microphone (3.5mm) | 11. HDMI 2.1 TMDS |
| 4. Card reader * | 12. 2x DisplayPort 1.4 |
| 5. Headphone / microphone combo jack (3.5mm) | 13. 4x USB 2.0 |
| 6. USB-C 3.2 Gen 1 | 14. 2x PS/2 ports (keyboard / mouse) * |
| 7. 2x USB 3.2 Gen 1 | 15. Ethernet (RJ-45) |
| 8. 2x USB 3.2 Gen 2 | 16. Optional ports on expansion cards * |
| | |

Notes:

- Ports with * are only available on selected models
- More ports are available through the optional expansion cards (not shown on the sample product above)

ThinkCentre M70s Gen 3

PERFORMANCE

Processor

Processor Family

Intel® Pentium®, or 12th Generation Intel Core™ i3 / i5 / i7 / i9 Processor

Processor

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics |
|-----------------------|-----------------------------|---------|----------------------------------|----------------------------------|-------|---------------------------|
| Pentium Gold G7400 | 2 | 4 | 3.7GHz | - | 6MB | Intel UHD Graphics 710 |
| Core i3-12100 | 4 (4 P-core + 0 E-core) | 8 | P-core 3.3GHz | P-core 4.3GHz | 12MB | Intel UHD Graphics 730 |
| Core i3-12300 | 4 (4 P-core + 0 E-core) | 8 | P-core 3.5GHz | P-core 4.4GHz | 12MB | Intel UHD Graphics 730 |
| Core i5-12400 | 6 (6 P-core + 0 E-core) | 12 | P-core 2.5GHz | P-core 4.4GHz | 18MB | Intel UHD Graphics 730 |
| Core i5-12400F | 6 (6 P-core + 0 E-core) | 12 | P-core 2.5GHz | P-core 4.4GHz | 18MB | - |
| Core i5-12500 | 6 (6 P-core + 0 E-core) | 12 | P-core 3.0GHz | P-core 4.6GHz | 18MB | Intel UHD Graphics 770 |
| Core i5-12600 | 6 (6 P-core + 0 E-core) | 12 | P-core 3.3GHz | P-core 4.8GHz | 18MB | Intel UHD Graphics 770 |
| Core i7-12700 | 12 (8 P-core + 4 E-core) | 20 | P-core 2.1GHz / E-core 1.6GHz | P-core 4.8GHz / E-core 3.6GHz | 25MB | Intel UHD Graphics 770 |
| Core i7-12700F | 12 (8 P-core + 4 E-core) | 20 | P-core 2.1GHz / E-core 1.6GHz | P-core 4.8GHz / E-core 3.6GHz | 25MB | - |
| Core i9-12900 | 16 (8 P-core + 8 E-core) | 24 | P-core 2.4GHz / E-core 1.8GHz | P-core 5.0GHz / E-core 3.8GHz | 30MB | Intel UHD Graphics 770 |
| Core i9-12900F | 16 (8 P-core + 8 E-core) | 24 | P-core 2.4GHz / E-core 1.8GHz | P-core 5.0GHz / E-core 3.8GHz | 30MB | - |

Operating System

Operating System

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Windows 10 IoT Enterprise LTSC 2021
- Ubuntu Linux
- No operating system

Graphics

Graphics^[1]

| Graphics | Туре | Memory Connector Max Resolution | | Key Features | Remark | |
|------------------------------|------------|---------------------------------|---|---|----------------|---|
| Intel UHD graphics 710 | Integrated | Shared | 2x DP 1.4 HBR2, 1x HDMI® 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI 2.1 TMDS / USB-C®) | 4096x2304@60hz(DP), 4096x2160@60Hz[HDMI / Flex IO(HDMI) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB-C)], 2048x1536@50Hz[Flex IO(VGA)] | DirectX® 12 | - |
| Intel UHD graphics 730 | Integrated | Shared | 2x DP 1.4 HBR2, 1x HDMI 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI 2.1 TMDS / USB- C) | 4096x2304@60hz(DP), 4096x2160@60Hz[HDMI / Flex IO(HD MI) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB-C)], 2048x1536@50Hz[Flex IO(VGA)] | DirectX 12 | - |

| Intel UHD graphics 770 | Integrated | Shared | HDMI 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / | 4096x2304@60hz(DP), 4096x2160@60Hz[HDMI / Flex IO(HD MI) / Flex IO(DP)], 3840x2160@60Hz[Flex IO(USB-C)], 2048x1536@50Hz[Flex IO(VGA)] | DirectX 12 | - |
|------------------------------|------------|--------|--|---|---------------|---|
|------------------------------|------------|--------|--|---|---------------|---|

Notes:

1. The information of integrated graphics are not applicable for the models without integrated graphics (for the details, please refer to processor section)

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays via onboard ports (2x DP, 1x HDMI, and 1x optional Flex IO), more displays support via discrete graphics

Notes:

1. Onboard video ports are only available for the models with integrated graphics

Chipset

Chipset

Intel Q670 chipset

Memory

Max Memory^[1]

Up to 128GB DDR4-3200

Memory Slots

Four DDR4 DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^{[1][2]}

Up to three drives, 1x 2.5"/3.5" HDD + 1x 2.5" HDD + 1x M.2 SSD

- 2.5" HDD up to 1TB each
- 3.5" HDD up to 2TB
- M.2 SSD up to 2TB

Storage Type

| Disk Type | Interface | | Offering | Security |
|---------------|------------------------------------|------|----------|----------|
| 2.5" SATA HDD | SATA 6Gb/s | 7.2K | - | - |
| 3.5" SATA HDD | SATA 6Gb/s | 7.2K | - | - |
| M.2 2242 SSD | PCIe® NVMe®, PCIe 3.0 x4 | - | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - | Opal |
| M.2 2280 SSD | PCIe NVMe, PCIe 4.0 x4 Value | - | - | Opal2 |
| M.2 2280 SSD | PCIe NVMe, PCIe 4.0 x4 Performance | - | - | Opal2 |

RAID

No support

Notes:

- 1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.
- 2. The max capacity of SSD/HDD is based on the test results with current Lenovo SSD/HDD offerings. The system may support more

capacity as the technology develops.

Removable Storage

Optical

- DVD-ROM, SATA connector, slim (9.0mm)
- DVD burner (DVD±RW), SATA connector, slim (9.0mm)

None Card Reader

- 3-in-1 card reader (SD, SDHC, SDXC)
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC897Q-CG codec

Speakers

Single speaker, 1W x1

Power Supply

Power Supply

| Power | Туре | Efficiency | Key Features |
|-------|-------|------------|-------------------|
| 180W | Fixed | 85% | 100V - 240V |
| 260W | Fixed | 90% | 100-240V, 50-60Hz |
| 310W | Fixed | 92% | 100-240V, 50-60Hz |
| 380W | Fixed | 92% | 100-240V, 50-60Hz |

DESIGN

Input Device

Keyboard

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black
- Lenovo Traditional Keyboard (USB connector), black
- No keyboard

Mouse

- Lenovo Calliope Mouse (USB connector), black
- Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
- Lenovo Mouse (PS/2 connector), black (only available via special bid)
- Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black
- No mouse

Mechanical

Form Factor

SFF (8.2L)

Dimensions (WxDxH)

93 x 298 x 340 mm (3.6 x 11.7 x 13.4 inches)

Weight^[1]

Around 5.3 kg (11.7 lbs)

Case Color

Black

Bays^[2]

- 1x 2.5" disk bay
- 1x 3.5" disk bay
- 1x slim ODD bay

Expansion Slots

- One PCIe 4.0 x16, low-profile, length \leq 155mm, height \leq 70mm
- Two PCIe 3.0 x1, low-profile, length ≤ 155mm, height ≤ 70mm
- Two M.2 slots (one for WLAN, one for SSD)

EOU

Toolless cover, disk, optical, extension card assembly / removal

Stand

- Vertical stand
- No stand

Others

- (Optional) Dust filter
- (Optional) Smart Cable (USB-A to USB-C)
- Supports Smart Power On

Notes:

1. Weight may vary by configuration.

2. 2.5" HDD tray is optional, or comes with 2.5 HDD. 3.5" bay supports 2.5" / 3.5" HDD, 3.5" to 2.5 converter comes with 2nd 2.5" HDD.

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Intel Ethernet Connection I219-LM, 1x RJ-45, supports Wake-on-LAN

Optional Ethernet

- Gigabit Ethernet, Bitland BN8E88, 1x RJ-45, PCIe x1
- 2.5 Gigabit Ethernet, Realtek RTL8125BGS, 1x RJ-45, PCIe x1
- No optional Ethernet

WLAN + Bluetooth®[1]

- Realtek RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Realtek Wi-Fi 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Intel Wireless-AC 9560, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- No WLAN and Bluetooth

Notes:

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation

Ports^{III}

Front Ports

- 2x USB 3.2 Gen 1
- 2x USB 3.2 Gen 2
- 1x USB-C 3.2 Gen 1 (15W charging)
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Optional Front Ports

1x card reader

Rear Ports^[2]

- 4x USB 2.0
- 1x HDMI 2.1 TMDS
- 2x DisplayPort[™] 1.4
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

Optional Rear Ports

- 1x USB-C 3.2 Gen 1 with DisplayPort function and 5V@3A charging (Flex IO)
- 1x HDMI 2.1 TMDS (Flex IO)
- 1x VGA (Flex IO)

ThinkCentre M70s Gen 3

Lenovo

- 1x DP 1.2 (Flex IO)
- 2x USB 3.2 Gen 1 (via 2-port USB expansion card, PCIe x1)
- 1x serial
- 1x 2nd serial
- 4x serial (via 4-port serial expansion card, PCIe x1)
- 1x parallel
- 2x PS/2

Notes:

- The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;
- USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
- USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
- USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
- Thunderbolt™ 3/4: 40 Gbit/s
- 2. For video ports on discrete graphics, please see graphics section

Monitor Cable

Monitor Cable

- DP to dual DP dongle
- DP to DVI-D dongle
- DP to HDMI 1.4 dongle
- DP to VGA cable (1.5M)
- DP to VGA dongle
- HDMI to VGA dongle
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

- (Optional) E-lock
- (Optional) Smart Cable Clip
- Kensington[®] Security Slot, 3 x 7 mm
- Padlock Loop

Chassis Intrusion Switch

- Chassis intrusion switch
- No chassis intrusion switch

Fingerprint Reader

- Touch style fingerprint reader on mouse
- No fingerprint reader

BIOS Security

- Administrator password
- Power-on password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Self-healing BIOS (Level 2)
- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- Individual USB port disablement

MANAGEABILITY

System Management

System Management^[1]

• Intel vPro Essentials

ThinkCentre M70s Gen 3

Lenovo

• Non-vPro

Notes:

1. Intel vPro offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty^[1]

- 1-year depot service
- 1-year limited onsite service
- 3-year limited onsite service
- No base warranty

Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

ENVIRONMENTAL

Operating Environment

Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications

Green Certifications

- (Optional) EPEAT[™] Gold
- (Optional) EPEAT Silver
- (Optional) ENERGY STAR[®] 8.0
- ErP Lot 3
- TCO Certified 9.0
- RoHS compliant

Other Certifications

Other Certifications

- (Optional) TÜV Rheinland® Low Noise
- (Optional) TÜV Rheinland Ultra Low Noise

Mil-Spec Test

MIL-STD-810H military test passed (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation, Contamination by Fluids, Salt Fog)

 Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.








intel





intel



intel



intel



intel